

Working Height Max.

13.8 m (45'3") 9.5 m (31'2")

Overall Lift Capacity Max.
Overall Width
Overall Length


1.18 m (3'10") 2.48 m (8'2")


320 kg (705 lb)

Overall Weight 2,800 kg (6,172 lb)

LS1212H Electric Scissor Lift H-Drive

LS1212H SPECIFICATIONS >>>







DIMENSIONS	
A. Working Height Max. (Indoor/Outdoor)	13.8 / 9.5 m (45'3" / 31'2")
B. Platform Height Max. (Indoor/Outdoor)	11.8 / 7.5 m (38'9" / 24'7")
C. Platform Height (Stowed)	1.48 m (4'10")
D. Platform Length	2.48 m (8'2")
E. Platform Width	1.15 m (3'9")
F. Extension Deck (Roll Out)	0.9 m (2'11")
G. Overall Length	2.48 m (8'2")
H. Overall Length (Without Ladder)	2.29 m (7'6")
I. Overall Width	1.18 m (3'10")
J. Stowed Height (Rails Up)	2.62 m (8'7")
K. Stowed Height (Rails Down)	2.1 m (6'11")
L. Wheelbase	1.88 m (6'2")
M. Ground Clearance (Pothole Raised)	100 mm (4")
N. Ground Clearance (Pothole Deployed)	20 mm (0.8")

PRODUCTIVITY	
Overall Lift Capacity Max.	320 kg (705 lb)
Extension Deck Capacity	120 kg (264 lb)
Platform Occupancy Max. (Indoor/Outdoor)	2/1
Drive Speed (Stowed)	2 km/h (1.2 mph)
Drive Speed (Raised)	0.4 km/h (0.2 mph)
Turning Radius (Inside/Outside)	0.24 / 2.3 m (9" / 7'6")
Lift/Lower Time	60 / 55 s
Gradeability	25 %
Tilt Sensor Activation	X 1.5° / Y 3°
Tire Size (Solid Non-marking)	381 x 127 mm (1'3" x 5")

V / 225 Ah
V / 230 Ah
24 V / 30 A
1 V / 3.3 kW
. (6 gal 4 pt)
. (5 gal 2 pt)

WEIGHT	
Overall Weight	2,800 kg (6,172 lb)